





Technical specification | Dordogne

Type : tufted non filled synthetic grass carpet

Yarn material : PE monofilament straight & PP monofilament curled

Yarn type : 7.200/8 dTex + 3.100/8 dTex

Yarn quality : environmental friendly, UV stabilized, UV stability meets DIN 53387 standard

 $: free\ of\ lead\ and\ cadmium$

Colour fastness : xenon test: blue scale > 7, grey-scale > 4

Primary backing : 100% PP Thiobac ® with fleece, black, UV stabilized

: weight 155 gr/m²

Secondary backing : black latex compound with a base of styrene-butadiene (SBR), with drainage holes

: weight 850 gr/m²

: 3/8" Tuft gauge Pile height : 26 mm (+/-10%) Stitches per 10cm : 15,0 (+/-10%) Stitches per m² : 15.750 (+/-10%) : 1.000 gr/m² Face weight (+/-10%) Total weight : 2.005 gr/m² (+/-10%)

 Roll width
 : 400cm + 200cm (+/- 2cm)

 Roll length
 : $25.20 m^{1}$ (+/- 20cm)

: roll length may vary

Water permeability : 60 liter/min/m²

Fire retardant classification : Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm)

: Efl-S1 (EN ISO 11925-2; non filled)

Batch information : before installation make sure the first 4 digits of the roll number are equal

Shrinkage : shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting

 $In fill\ recommendation \\ \hspace{2cm} : non\ in fill\ (optional\ 5kg/m^2)$

Avalon has the right to alter each product specification in order to improve the artificial grass according to the newest technological applications.

Avalon is not legally liable in case of non-compliance with the above mentioned specifications.

all quotations, transactions and deliveries are confirmed in our general conditions of sales